


Date
Customer
Project
Type

*FFD\_Medard Surface Adjustable 70 1x LED 1800-3000K WD Medium Trailing Edge DI White Structure*



**Specifications**

Material	12732309
Light Source Type	LED
LED Type	BRIDGELUX WARMDIM 12W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 81
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	26.0
Input Voltage	230V
Luminaire power (W)	13.5
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Surface
Adjustability	H 360° V 360°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	1186.0
Luminous flux per lamp (lm)	802
Efficacy (lm/W)	59
Glare rating	17
Remark	• 4000K on request

The quirky long legs of the praying mantis inspired the Dutch Basten Leijh Design Studio for the creation of Medard, its initial design being a stylish table lamp. Now a large, versatile family of accent lights, and a lot of flexibility, Medard opens into a multitude of elegant applications.

**TM30 & CRI diagram**



**Light distribution & beam diagram**

