

Pate	
Customer	
Project	
уре	

Medard Track 230V Adjustable 70 1x LED 3000K Flood DALI DI Black Structure



The quirky long legs of the praying mantis inspired the Dutch Basten Leijh Design Studio for the creation of Medard, its initial design being a stylish table lamp. Now a large, versatile family of accent lights, and a lot of flexibility, Medard opens into a multitude of elegant applications.





C	- : /': -		
$\mathbf{N} \mathbf{n} \boldsymbol{\rho}$	CITIC	αm	$n \varsigma$
$\cup \rho \cup$	cific	aiio	$\iota\iota\iota$

Material Material	12737432		
Light Source Type	LED		
LED Type	BRIDGELUX VERO13		
LED technology	LED COB		
CRI	Min. 90		
Colour Temperature	3000K		
Lifetime	L80B20 @50,000 Hours		
Lamp Included	Yes		
Number of Light Sources	1		
CIE flux code	100 100 100 100 84		
Binning (SDCM)	3		
Light Direction	Down		
Optic	Reflector		
Measured beam angle (°)	38.0		
Input Voltage	230V		
Luminaire power (W)	13.0		
Electrical Class	T		
IP Rating	20		
Glow wire rating (°C)	960		
Dimming Protocol	DALI		
DALI Standard	DALI-2		
Indoor/Outdoor	Indoor		
Application	Ceiling		
Adjustability	H 355° V 360°		
Distance to Lighted Object (m)	0,1		
Primary Colour & Primary Finish	Black, Structure		
Gross weight (g)	1152.0		
Delivered lumens (Im)	879		
Efficacy (lm/W)	67		
Glare rating	16		
Remark	 4000K on request This is not a complete product. Track 230V system required. 		



TM30 & CRI diagram





Light distribution & beam diagram

