


| |
|----------|
| Date |
| Customer |
| Project |
| Type |

*FFD_Rektor Surface Adjustable 78x78 1x LED 1800-3000K WD Medium Trailing Edge DI White Structure - Bronze
Brushed Anodised*



With a name derived from the Latin word for “ruler”, the Rektor family has all the qualities of a leader. Strong, guiding, and arguably a good listener. Winner of the 2014 Henry Van de Velde design award, Rektor is an orientable downlighter that showcases the distinguished effects of right angles and accented light direction.



Specifications

| | |
|-------------------------------------|--------------------------|
| Material | 12826266 |
| Light Source Type | LED |
| LED Type | BRIDGELUX WARMDIM 12W |
| LED technology | LED COB |
| CRI | Min. 95 |
| Colour Temperature | 1800-3000K (Warm Dim) |
| Lifetime | L80B10 @50,000 Hours |
| Lamp Included | Yes |
| Number of Light Sources | 1 |
| Binning (SDCM) | 3 |
| Light Direction | Down |
| Optic | Reflector |
| Measured beam angle (°) | 26.0 |
| Input Voltage | 230V |
| Luminaire power (W) | 13.5 |
| Electrical Class | I |
| IP Rating | 20 |
| Glow wire rating (°C) | 960 |
| Dimming Protocol | Trailing Edge |
| Indoor/Outdoor | Indoor |
| Application | Ceiling, Wall |
| Mounting | Surface |
| Adjustability | H 360° V -90°/+90° |
| Distance to Lighted Object (m) | 0,1 |
| Primary Colour & Primary Finish | White, Structure |
| Secondary Colour & Secondary Finish | Bronze, Brushed Anodised |
| Gross weight (g) | 1427.0 |
| Luminous flux per lamp (lm) | 881 |
| Efficacy (lm/W) | 65 |
| Glare rating | 20 |

TM30 & CRI diagram



Light distribution & beam diagram

