



Date
Customer
Project
Type

Smart Lotis Recessed 48 lx HO IP55 LED 3000K Medium DE Black Structure




The 3 original designs, Smart Kup, Lotis and Cake still manage to steal the hearts of interior designers. And this goes for the entire Smart family. Smart's accessibility and extreme versatility are arguably fit for any expression. Mix and match accent lighting, up and downlight, fixed or adjustable, a mosaic of shapes, sizes, colours and mounting options, and create a playful installation.




Specifications

Material	12862032
Light Source Type	LED
LED Type	CREE 1304
LED technology	LED COB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	99 100 100 100 69
Binning (SDCM)	2
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	26.3
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	55
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Recessed
Cut-out size (mm)	ø44
Mounting depth (mm)	52.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	130.0
Drive current (mA)	350 500
Min. forward voltage (Vf)	7,5 7,8
Max. forward voltage (Vf)	9,5 9,8
Connected load (W)	3,0 4,4
Delivered lumens (lm)	215 290
Efficacy (lm/W)	72 72
Glare rating	1 1

TM30 & CRI diagram




Light distribution & beam diagram




Diagrams



Decorative Accessories




- 13350009** Mask Smart 48 1x White Structure
13350032 Mask Smart 48 1x Black Structure
13350046 Mask Smart 48 1x Gold Matt




- 13350109** Mask Smart 48 2x White Structure
13350132 Mask Smart 48 2x Black Structure
13350146 Mask Smart 48 2x Gold Matt


Installation Accessories



- 12293730** Plaster Kit 44 1x



- 10889530** Installation Housing 123x100x80



- 12290730** Plaster Kit 100x120-45 1x

Choose a required accessory



MODULAR
LIGHTING —
INSTRUMENTS

Smart Lotis Recessed 48 lx HO IP55 LED 3000K Medium DE
Black Structure
