


Date
Customer
Project
Туре

Smart Lotis Recessed 48 1x HO IP55 LED 2700K Medium DE Black Structure



The 3 original designs, Smart Kup, Lotis and Cake still manage to steal the hearts of interior designers. And this goes for the entire Smart family. Smart's accessibility and extreme versatility are arguably fit for any expression. Mix and match accent lighting, up and downlight, fixed or adjustable, a mosaic of shapes, sizes, colours and mounting options, and create a playful installation.





Specifications				
Material	12862132			
Light Source Type	LED			
LED Type	CREE 1304			
LED technology	LED COB			
CRI	Min. 90			
Colour Temperature	2700K			
Lifetime	L90B10 @50,000 Hours			
Lamp Included	Yes			
Number of Light Sources	1			
CIE flux code	99 100 100 100 69			
Binning (SDCM)	2			
Light Direction	Down			
Optic	Reflector			
Measured beam angle (°)	26.3			
Input Voltage	Constant C	Current Driv	er Required	
Electrical Class	III			
IP Rating	55			
Glow wire rating (°C)	960			
Indoor/Outdoor	Indoor			
Application	Ceiling, Wa	all		
Mounting	Recessed			
Cut-out size (mm)	ø44			
Mounting depth (mm)	60.0			
Adjustability	Not Applica	able		
Distance to Lighted Object (m)	0,1			
Primary Colour & Primary Finish	Black, Stru	ıcture		
Gross weight (g)	130.0			
Drive current (mA)	350	500		
Min. forward voltage (Vf)	7,5	7,8		
Max. forward voltage (Vf)	9,5	9,8		
Connected load (W)	3,0	4,4		
Luminous flux per lamp (lm)	215	290		
Efficacy (Im/W)	72	72		
Glare rating	1	1		




TM30 & CRI diagram





Light distribution & beam diagram






Decorative Accessories



13350009Mask Smart 48 1x White Structure13350032Mask Smart 48 1x Black Structure13350046Mask Smart 48 1x Gold Matt




 13350109
 Mask Smart 48 2x White Structure


 13350132
 Mask Smart 48 2x Black Structure

 13350146
 Mask Smart 48 2x Gold Matt


Installation Accessories



12293730 Plaster Kit 44 1x



10889530 Installation Housing 123x100x80



12290730 Plaster Kit 100x120-45 1x

Choose a required accessory

