


Date
Customer
Project
Type

*Smart Lotis Asy Recessed 48 1x HO IP55 LED 3000K Medium DE White Structure*



**Specifications**


Material	12892009
Light Source Type	LED
LED Type	CREE 1304
LED technology	LED COB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	89 97 99 100 66
Binning (SDCM)	2
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	25.7
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	55
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Recessed
Cut-out size (mm)	ø44
Mounting depth (mm)	60.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	114.0
Drive current (mA)	350      500
Min. forward voltage (Vf)	7,5      7,8
Max. forward voltage (Vf)	9,5      9,8
Connected load (W)	3,0      4,4
Luminous flux per lamp (lm)	206      279
Efficacy (lm/W)	69      69
Glare rating	16      16

The 3 original designs, Smart Kup, Lotis and Cake still manage to steal the hearts of interior designers. And this goes for the entire Smart family. Smart's accessibility and extreme versatility are arguably fit for any expression. Mix and match accent lighting, up and downlight, fixed or adjustable, a mosaic of shapes, sizes, colours and mounting options, and create a playful installation.

**TM30 & CRI diagram**



**Light distribution & beam diagram**



Diagrams

**Decorative Accessories**



- 13350009** Mask Smart 48 1x White Structure
- 13350032** Mask Smart 48 1x Black Structure
- 13350046** Mask Smart 48 1x Gold Matt



- 13350109** Mask Smart 48 2x White Structure
- 13350132** Mask Smart 48 2x Black Structure
- 13350146** Mask Smart 48 2x Gold Matt

**Installation Accessories**



- 12293730** Plaster Kit 44 1x



- 10889530** Installation Housing 123x100x80



- 12290730** Plaster Kit 100x120-45 1x

Choose a required accessory

