


Date
Customer
Project
Type

## FFD\_Single Round Track 230V Adjustable 122 1x LED 2700K Flood Trailing Edge DI Black Structure

Playing with square-angled and round shapes, Single Round combines the best of both worlds. The M-LED 111 module fits well in our stylish aluminium cylinder. The single connection with the hinge contributes to a highly directional fixture. A great solution for use in specific retail projects thanks to high performing and energy-efficient LED technology.



### Specifications

Material	13031632
Light Source Type	LED
LED Type	BRIDGELUX VERO13
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	41.3
Input Voltage	230V
Luminaire power (W)	28.5
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Ceiling
Adjustability	H 360° V -90°/+90°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	1772.0
Delivered lumens (lm)	1913
Efficacy (lm/W)	67
Glare rating	19
Remark	<ul style="list-style-type: none"> <li>This is not a complete product. Track 230V system required.</li> </ul>

### TM30 & CRI diagram



### Light distribution & beam diagram

