


| |
|----------|
| Date |
| Customer |
| Project |
| Type |

Wink Recessed 115 1x IP54 LED 2700K Medium DE Black Structure



Specifications


| | |
|---------------------------------|----------------------------------|
| Material | 13070332 |
| Light Source Type | LED |
| LED Type | BRIDGELUX VERO13 |
| LED technology | LED COB |
| CRI | Min. 90 |
| Colour Temperature | 2700K |
| Lifetime | L80B20 @50,000 Hours |
| Lamp Included | Yes |
| Number of Light Sources | 1 |
| Binning (SDCM) | 3 |
| Light Direction | Down |
| Optic | Reflector |
| Measured beam angle (°) | 22.8 |
| Input Voltage | Constant Current Driver Required |
| Electrical Class | III |
| IP Rating | 54 |
| Glow wire rating (°C) | 960 |
| Indoor/Outdoor | Indoor |
| Application | Ceiling |
| Mounting | Recessed |
| Cut-out size (mm) | ø133 |
| Mounting depth (mm) | 100.0 |
| Adjustability | H 355° |
| Distance to Lighted Object (m) | 0,1 |
| Primary Colour & Primary Finish | Black, Structure |
| Gross weight (g) | 859.0 |
| Drive current (mA) | 350 500 700 |
| Min. forward voltage (Vf) | 29,1 29,9 31,0 |
| Max. forward voltage (Vf) | 33,7 34,7 35,8 |
| Connected load (W) | 11,0 16,2 23,4 |
| Luminous flux per lamp (lm) | 831 1140 1517 |
| Efficacy (lm/W) | 76 71 66 |
| Glare rating | 15 16 17 |

Wink may be recessed and subtle, but its technical ingenuity is nothing short of remarkable. And so is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out. Wink 82 also fits with Wink flange, a low ring around the spot.

Remark

- This is not a complete product. Recessed Ring or Wink Flange required.
-

TM30 & CRI diagram



Installation Accessories



- **13073009** Ring Recessed 115 Wink White Structure
- **13073032** Ring Recessed 115 Wink Black Structure



- **14204030** Ring Recessed Trimless 146 1x
- Choose a required accessory