


Date
Customer
Project
уре

Wink Asy Recessed 115 1x IP54 LED 3000K Flood DE White Structure



Wink may be recessed and subtle, but its technical ingenuity is nothing short of remarkable. And so is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out. Wink 82 also fits with Wink flange, a low ring around the spot.





Specifications				
Material	13071709			
Light Source Type	LED			
LED Type	BRIDGELUX VERO13 G8			
LED technology	LED COB			
CRI	Min. 90			
Colour Temperature	3000K			
Lifetime	L80B10 @50,000 Hours			
Lamp Included	Yes			
Number of Light Sources	1			
CIE flux code	70 95 99 100 82			
Binning (SDCM)	2			
Light Direction	Down			
Optic	Reflector			
Measured beam angle (°)	41.0			
Input Voltage	Constant Current Driver Required			
Electrical Class	III			
IP Rating	54			
Glow wire rating (°C)	960			
Indoor/Outdoor	Indoor			
Application	Ceiling			
Mounting	Recessed			
Cut-out size (mm)	ø133			
Mounting depth (mm)	100.0			
Adjustability	H 355°			
Distance to Lighted Object (m)	0,1			
Primary Colour & Primary Finish	White, Structure			
Gross weight (g)	871.0			
Drive current (mA)	350	500	700	
Min. forward voltage (Vf)	28,3	29,0	29,7	
Max. forward voltage (Vf)	32,9	33,6	34,5	
Connected load (W)	10,7	15,7	22,5	
Luminous flux per lamp (lm)	1206	1646	2153	
Efficacy (Im/W)	113	105	96	
Glare rating	15	16	17	

• This is not a complete product. Recessed Ring

Remark





or Wink Flange required.




TM30 & CRI diagram








Installation Accessories



13073009 Ring Recessed 115 Wink White Structure13073032 Ring Recessed 115 Wink Black Structure



14204030 Ring Recessed Trimless 146 1x

Choose a required accessory