


Date
Customer
Project
Туре

FFD_Lotis Round Recessed 82 1x M-LED DE Gold Brushed Anodised



Lotis Round is a recessed spotlight with a slight trim. The hallmark of this luminaire is its deeply recessed cone, which holds the light source. Known for its effortless design and high functionality, Lotis Round comes in different diameters and with various types of light sources.






Specifications Material

Material	13080046
Light Source Type	M-LED
Lifetime	L80B20 @50,000 Hours
Lamp Included	No
Number of Light Sources	1
Light Direction	Down
Optic	Reflector
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Recessed
Cut-out size (mm)	ø76
Mounting depth (mm)	95.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Gold, Brushed Anodised
Gross weight (g)	92.0
Drive current (mA)	350
Luminous flux per lamp (lm)	409
Efficacy (Im/W)	66
Remark	This is not a complete product. Light module required.




M-LED Module




4.400000=	MALED MALLED GROOM OF A PERMITTED OF
14060005	M-LED Module 50 1x LED 2700K Spot DE Aluminium Brushed Anodised
14060105	M-LED Module 50 1x LED 2700K Medium DE Aluminium Brushed Anodised
14060205	M-LED Module 50 1x LED 2700K Flood DE Aluminium Brushed Anodised
14060305	M-LED Module 50 1x LED 3000K Spot DE Aluminium Brushed Anodised
14060405	M-LED Module 50 1x LED 3000K Medium DE Aluminium Brushed Anodised
14060505	M-LED Module 50 1x LED 3000K Flood DE Aluminium Brushed Anodised
14060905	M-LED Module 50 1x LED 4000K Spot DE Aluminium Brushed Anodised
14061005	M-LED Module 50 1x LED 4000K Medium DE Aluminium Brushed Anodised
14061105	M-LED Module 50 1x LED 4000K Flood DE Aluminium Brushed Anodised
14061205	M-LED Module 50 1x LED 1800-3000K WD Spot DE Aluminium Brushed Anodised
14061305	M-LED Module 50 1x LED 1800-3000K WD Medium DE Aluminium Brushed Anodised
14061405	M-LED Module 50 1x LED 1800-3000K WD Flood DE Aluminium Brushed Anodised

Installation Accessories



10889830 Installation Housing 192x190x130



12290830 Plaster Kit 190X190 - 76 1x

Choose a required accessory