


Lotis Round Recessed 86 Ix IP55 M-LED DE Black Structure



Specifications

Material	13090008
Light Source Type	M-LED
Lifetime	L80B20 @50,000 Hours
Lamp Included	No
Number of Light Sources	1
Light Direction	Down
Optic	Reflector
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	55
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Recessed
Cut-out size (mm)	Ø79
Mounting depth (mm)	95.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	201.0
Drive current (mA)	350
Luminous flux per lamp (lm)	398
Efficacy (lm/W)	64
Remark	• This is not a complete product. Light module required.

Lotis Round is a recessed spotlight with a slight trim. The hallmark of this luminaire is its deeply recessed cone, which holds the light source. Known for its effortless design and high functionality, Lotis Round comes in different diameters and with various types of light sources.

M-LED Module


- **14060005** M-LED Module 50 1x LED 2700K Spot DE Aluminium Brushed Anodised
- **14060105** M-LED Module 50 1x LED 2700K Medium DE Aluminium Brushed Anodised
- **14060205** M-LED Module 50 1x LED 2700K Flood DE Aluminium Brushed Anodised
- **14060305** M-LED Module 50 1x LED 3000K Spot DE Aluminium Brushed Anodised
- **14060405** M-LED Module 50 1x LED 3000K Medium DE Aluminium Brushed Anodised
- **14060505** M-LED Module 50 1x LED 3000K Flood DE Aluminium Brushed Anodised
- **14060905** M-LED Module 50 1x LED 4000K Spot DE Aluminium Brushed Anodised
- **14061005** M-LED Module 50 1x LED 4000K Medium DE Aluminium Brushed Anodised
- **14061105** M-LED Module 50 1x LED 4000K Flood DE Aluminium Brushed Anodised
- **14061205** M-LED Module 50 1x LED 1800-3000K WD Spot DE Aluminium Brushed Anodised
- **14061305** M-LED Module 50 1x LED 1800-3000K WD Medium DE Aluminium Brushed Anodised
- **14061405** M-LED Module 50 1x LED 1800-3000K WD Flood DE Aluminium Brushed Anodised

Installation Accessories


10889830 Installation Housing 192x190x130

12290230 Plaster Kit 190X190 - 80 1x

■ Choose a required accessory