


| Date     |
|----------|
| Customer |
| Project  |
| Туре     |

## Lotis Round Recessed 86 1x IP55 M-LED DE White Structure



Lotis Round is a recessed spotlight with a slight trim. The hallmark of this luminaire is its deeply recessed cone, which holds the light source. Known for its effortless design and high functionality, Lotis Round comes in different diameters and with various types of light sources.






| $\alpha$ |    |     | c.           |     |          | 4 |
|----------|----|-----|--------------|-----|----------|---|
| V 7      | n0 | C11 | 110          | ati | on.      | C |
| ונ       | ノヒ | υı  | $\iota\iota$ | uıı | $O_{II}$ | ) |
|          |    |     |              |     |          |   |

| Material                          | 13090009   |
|-----------------------------------|--|
| Light Source Type                 | M-LED  |
| Lifetime                          | L80B20 @50,000 Hours                                   |
| Lamp Included                     | No   |
| Number of Light<br>Sources        | 1  |
| Light Direction                   | Down   |
| Optic                             | Reflector  |
| Input Voltage                     | Constant Current Driver Required                       |
| Electrical Class                  | III  |
| IP Rating                         | 55   |
| Glow wire rating (°C)             | 960  |
| Indoor/Outdoor                    | Indoor   |
| Application                       | Ceiling, Wall  |
| Mounting                          | Recessed   |
| Cut-out size (mm)                 | ø79  |
| Mounting depth (mm)               | 95.0   |
| Adjustability                     | Not Applicable   |
| Distance to Lighted<br>Object (m) | 0,1  |
| Primary Colour & Primary Finish   | White, Structure                                       |
| Gross weight (g)                  | 161.0  |
| Drive current (mA)                | 350  |
| Luminous flux per lamp (lm)       | 459  |
| Efficacy (Im/W)                   | 74   |
| Remark                            | This is not a complete product. Light module required. |




## M-LED Module



| 14060005 | M-LED Module 50 1x LED 2700K Spot DE Aluminium Brushed Anodised           |
|----------|---|
| 14060105 | M-LED Module 50 1x LED 2700K Medium DE Aluminium Brushed Anodised         |
| 14060205 | M-LED Module 50 1x LED 2700K Flood DE Aluminium Brushed Anodised          |
| 14060305 | M-LED Module 50 1x LED 3000K Spot DE Aluminium Brushed Anodised           |
| 14060405 | M-LED Module 50 1x LED 3000K Medium DE Aluminium Brushed Anodised         |
| 14060505 | M-LED Module 50 1x LED 3000K Flood DE Aluminium Brushed Anodised          |
| 14060905 | M-LED Module 50 1x LED 4000K Spot DE Aluminium Brushed Anodised           |
| 14061005 | M-LED Module 50 1x LED 4000K Medium DE Aluminium Brushed Anodised         |
| 14061105 | M-LED Module 50 1x LED 4000K Flood DE Aluminium Brushed Anodised          |
| 14061205 | M-LED Module 50 1x LED 1800-3000K WD Spot DE Aluminium Brushed Anodised   |
| 14061305 | M-LED Module 50 1x LED 1800-3000K WD Medium DE Aluminium Brushed Anodised |
| 14061405 | M-LED Module 50 1x LED 1800-3000K WD Flood DE Aluminium Brushed Anodised  |

## Installation Accessories



**10889830** Installation Housing 192x190x130

**12290230** Plaster Kit 190X190 - 80 1x

Choose a required accessory