


Date
Customer
Project
Type

Lotis Round Recessed Adjustable 97 1x M-LED DE Aluminium Matt




Lotis Round è un faretto incassato dal profilo discreto. La caratteristica distintiva di questo apparecchio illuminante è il suo cono profondamente incassato, che contiene la fonte luminosa. Noto per il suo design semplice e la grande funzionalità, Lotis Round è disponibile in diversi diametri e con varie tipologie di fonti luminose.



Specifications


Materiale	13100005
Tipo di Sorgente	M-LED
Vita utile	L80B20 @50.000 ore
Lampadina inclusa	No
Numero di fonte luminosa	1
Direzione della luce	Diretta
Ottiche	Riflettore
Volt in ingresso	Necessario driver a corrente costante
Classificazione elettrica	III
Grado IP	20
Test filo a caldo (°C)	960
Interno/Esterno	Interno
Applicazione	Soffitto
Montaggio	Incassato
Foro d'incasso (mm)	Ø92
Profondità di montaggio (mm)	100,0
Orientabilità	V -15°/+15°
Distanza dall'oggetto illuminato (m)	0,1
Colore primario & Finitura primaria	Alluminio, Opaca
Peso lordo (g)	120,0
Corrente di azionamento (mA)	350
Flusso reale in uscita (lm)	501
Efficienza (lm/W)	81

Modulo M-LED



- **14060005** M-LED Module 50 1x LED 2700K Spot DE Aluminium Brushed Anodised
- **14060105** M-LED Module 50 1x LED 2700K Medium DE Aluminium Brushed Anodised
- **14060205** M-LED Module 50 1x LED 2700K Flood DE Aluminium Brushed Anodised
- **14060305** M-LED Module 50 1x LED 3000K Spot DE Aluminium Brushed Anodised
- **14060405** M-LED Module 50 1x LED 3000K Medium DE Aluminium Brushed Anodised
- **14060505** M-LED Module 50 1x LED 3000K Flood DE Aluminium Brushed Anodised
- **14060905** M-LED Module 50 1x LED 4000K Spot DE Aluminium Brushed Anodised
- **14061005** M-LED Module 50 1x LED 4000K Medium DE Aluminium Brushed Anodised
- **14061105** M-LED Module 50 1x LED 4000K Flood DE Aluminium Brushed Anodised
- **14061205** M-LED Module 50 1x LED 1800-3000K WD Spot DE Aluminium Brushed Anodised
- **14061305** M-LED Module 50 1x LED 1800-3000K WD Medium DE Aluminium Brushed Anodised
- **14061405** M-LED Module 50 1x LED 1800-3000K WD Flood DE Aluminium Brushed Anodised

Accessori Installazione



10889830 Installation Housing 192x190x130

12290330 Plaster Kit 190X190 - 92 1x

■ Choose a required accessory