


|          |
|----------|
| Date     |
| Customer |
| Project  |
| Type     |

*Charlatan Track 230V Adjustable 85 lx LED 2700K DALI DI Black Structure*



A trackspot for our 230V track rail, Charlatan is an easy choice for spaces that need change. Its unpretentious, timeless design and excellent price/quality ratio make Charlatan ideal for several spaces. A thin, adjustable bracket. A flexibility of 360° horizontal and 90° vertical. A deeper-recessed reflector for visual comfort. With Charlatan, there's no compromise on quality or technology.




**Specifications**

|                                 |  |
|---------------------------------|--|
| Material                        | 13111432   |
| Light Source Type               | LED  |
| LED Type                        | LUMILED 1208 GEN 4   |
| LED technology                  | LED COB  |
| CRI                             | Min. 90  |
| Colour Temperature              | 2700K  |
| Lifetime                        | L80B10 @50,000 Hours   |
| Lamp Included                   | Yes  |
| Number of Light Sources         | 1  |
| CIE flux code                   | 100 100 100 100 80   |
| Binning (SDCM)                  | 3  |
| Light Direction                 | Down   |
| Optic                           | Reflector  |
| Input Voltage                   | 230V   |
| Luminaire power (W)             | 27.5   |
| Electrical Class                | I  |
| IP Rating                       | 20   |
| Glow wire rating (°C)           | 960  |
| Dimming Protocol                | DALI   |
| DALI Standard                   | DALI-2   |
| Indoor/Outdoor                  | Indoor   |
| Application                     | Ceiling  |
| Adjustability                   | H 359° V -90°/+90°   |
| Distance to Lighted Object (m)  | 0,1  |
| Primary Colour & Primary Finish | Black, Structure   |
| Gross weight (g)                | 1052.0   |
| Luminous flux per lamp (lm)     | 2306   |
| Efficacy (lm/W)                 | 83   |
| Glare rating                    | 14   |
| Remark                          | <ul style="list-style-type: none"> <li>• 3500K on request</li> <li>• Reflector not included</li> <li>• 3500K on request</li> <li>• Reflector not included</li> <li>• This is not a complete product. Reflector and track 230V system required.</li> <li>• This is not a complete product. Reflector and track 230V system required.</li> </ul> |



*Optical Accessories*



- **10210006** Reflector 85 Flood Aluminium Anodised
- **10210004** Reflector 85 Spot Aluminium Anodised
- **10210005** Reflector 85 Medium Aluminium Anodised

■ Choose a required accessory