


Date
Customer
Project
Туре

Charlatan Track 230V Adjustable 100 1x LED 4000K Trailing Edge DI White Structure



A trackspot for our 230V track rail, Charlatan is an easy choice for spaces that need change. Its unpretentious, timeless design and excellent price/quality ratio make Charlatan ideal for several spaces. A thin, adjustable bracket. A flexibility of 360° horizontal and 90° vertical. A deeper-recessed reflector for visual comfort. With Charlatan, there's no compromise on quality or technology.



Specifications

specifications	
Material	13112309
Light Source Type	LED
LED Type	LUMILED 1211 GEN4
LED technology	LED COB
CRI	Min. 90
Colour Temperature	4000K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	99 100 100 100 85
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Input Voltage	230V
Luminaire power (W)	34.5
Electrical Class	
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Ceiling
Adjustability	H 359° V -90°/+90°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	1305.0
Luminous flux per lamp (lm)	3666
Efficacy (Im/W)	106
Glare rating	19
Remark	 3500K on request Reflector not included 3500K on request Reflector not included This is not a complete product. Reflector and track 230V system required. This is not a complete product. Reflector and track 230V system required.




TM30 & CRI diagram



	CRI					93.8					
	F	R9				7					
-	0	10	20	30	40	50	60	70	80	90	100
R1	95										
R2	99										
	97	-	- 22	- 02		- 10		10	- 11	- 11	
	91										
R5	93			_	_		_				
	95			1							
R7	92				100						
R8	87										
	75		- 25		110						
R10	98	_	_	_	_	_	_	_	_	_	
R11	92							_	_	1	
	72	-			_						
R13	98	_		_		_	_				
	100	-									
R15	93	1				- 19		18		35	



Optical Accessories



10210009 Reflector 100 Flood Aluminium Anodised

- 10210008 Reflector 100 Medium Aluminium Anodised
- 10210007 Reflector 100 Spot Aluminium Anodised

Choose a required accessory