


Date
Customer
Project
Type

Charlatan Track 230V Adjustable 100 lx LED 4000K Trailing Edge DI White Structure




Specifications

Material	13112309
Light Source Type	LED
LED Type	LUMILED 1211 GEN4
LED technology	LED COB
CRI	Min. 90
Colour Temperature	4000K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	99 100 100 100 85
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Input Voltage	230V
Luminaire power (W)	34.5
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Ceiling
Adjustability	H 360° V 0°/+90°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	1305.0
Luminous flux per lamp (lm)	3666
Efficacy (lm/W)	106
Glare rating	19
Remark	<ul style="list-style-type: none"> • 3500K on request • Reflector not included • 3500K on request • Reflector not included • This is not a complete product. Reflector and track 230V system required. • This is not a complete product. Reflector and track 230V system required.

TM30 & CRI diagram



Optical Accessories



- **10210009** Reflector 100 Flood Aluminium Anodised
- **10210008** Reflector 100 Medium Aluminium Anodised
- **10210007** Reflector 100 Spot Aluminium Anodised

■ Choose a required accessory