

---




---





---




---

*K 120 Recessed Adjustable 120 Ix LED 2700K Medium DE Black Structure*

**Specifications**


Material	13340132		
Light Source Type	LED		
LED Type	LUMILED 1205 GEN 3		
LED technology	LED COB		
CRI	Min. 90		
Colour Temperature	2700K		
Lifetime	L80B20 @50,000 Hours		
Lamp Included	Yes		
Number of Light Sources	1		
Binning (SDCM)	3		
Light Direction	Down		
Optic	Reflector		
Measured beam angle (°)	23.3		
Input Voltage	Constant Current Driver Required		
Electrical Class	III		
IP Rating	20		
Glow wire rating (°C)	960		
Indoor/Outdoor	Indoor		
Application	Ceiling, Wall		
Mounting	Recessed		
Cut-out size (mm)	Ø114		
Mounting depth (mm)	200.0		
Adjustability	H 359° V 45°		
Distance to Lighted Object (m)	0,1		
Primary Colour & Primary Finish	Black, Structure		
Gross weight (g)	468.0		
Drive current (mA)	350	500	700
Min. forward voltage (Vf)	30,9	31,9	33,2
Max. forward voltage (Vf)	35,7	36,8	38,3
Connected load (W)	11,7	17,2	25,0
Luminous flux per lamp (lm)	1186	1608	2105
Efficacy (lm/W)	101	94	84
Glare rating	17	18	19

**TM30 & CRI diagram**

**Light distribution & beam diagram**



### *Optical Accessories*



**10216903** Spreadlens 80



**10212802** Honeycomb 80 Black Matt



**10217002** Crossblade 80 Black Matt

Choose a required accessory