





United Surface 1274 1x LED 2700K Non-Dim DI Black Matt

Specifications

Material	13390002
Light Source Type	LED
LED Type	NLP
LED technology	LED PCB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
Binning (SDCM)	2
Light Direction	Down
Input Voltage	230V
Luminaire power (W)	22.0
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Non-Dim
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Surface
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Matt
Gross weight (g)	2300.0
Luminous flux per lamp (lm)	926
Efficacy (lm/W)	42
Glare rating	25

Our Good Design Award-winning United luminaire continues to be a testament to the simple beauty of the fluorescent lamp. That being said, this LED luminaire is anything but ordinary, with a U-shaped housing that is both ceiling and wall-mountable. The light tubes of United are slightly recessed into the housing, emitting light on all sides, including both ends.

TM30 & CRI diagram

Light distribution & beam diagram



Decorative Accessories



13392032 Cover 1274 1x United Black Structure


13392009 Cover 1274 1x United White Structure

Installation Accessories



11060709 Power Feed and Suspension Kit 4000 Round 3P United (2) Straight White Structure

11060732 Power Feed and Suspension Kit 4000 Round 3P United (2) Straight Black Structure



11061709 Power Feed and Suspension Kit 4000 Round 5P United (2) Straight White Structure

11061732 Power Feed and Suspension Kit 4000 Round 5P United (2) Straight Black Structure

 Choose a required accessory