
Date

Customer


Project

Type

United Surface 1274 1x LED 2700K Non-Dim DI White Structure




Our Good Design Award-winning United luminaire continues to be a testament to the simple beauty of the fluorescent lamp. That being said, this LED luminaire is anything but ordinary, with a U-shaped housing that is both ceiling and wall-mountable. The light tubes of United are slightly recessed into the housing, emitting light on all sides, including both ends.




Specifications

Material	13390009
Light Source Type	LED
LED Type	NLP
LED technology	LED PCB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
Binning (SDCM)	2
Light Direction	Down
Input Voltage	230V
Luminaire power (W)	22.0
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Non-Dim
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Surface
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	2300.0
Delivered lumens (lm)	1470
Efficacy (lm/W)	66
Glare rating	26


TM30 & CRI diagram



Light distribution & beam diagram




Decorative Accessories




- 13392032** Cover 1274 1x United Black Structure
- 13392009** Cover 1274 1x United White Structure

Installation Accessories



- 11060709** Power Feed and Suspension Kit 4000 Round 3P United (2) Straight White Structure
- 11060732** Power Feed and Suspension Kit 4000 Round 3P United (2) Straight Black Structure



- 11061709** Power Feed and Suspension Kit 4000 Round 5P United (2) Straight White Structure
- 11061732** Power Feed and Suspension Kit 4000 Round 5P United (2) Straight Black Structure

Choose a required accessory