


Date
Customer
Project
Type

FFD_United Surface 974 2x LED 2700K 1-10V DI Black Matt



Specifications


Material	13393402
Light Source Type	LED
LED Type	NLP
LED technology	LED PCB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
Binning (SDCM)	2
Light Direction	Down
Input Voltage	230V
Luminaire power (W)	31.0
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	1-10V
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Surface
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Matt
Gross weight (g)	3215.0
Luminous flux per lamp (lm)	1339
Efficacy (lm/W)	43
Glare rating	27

Our Good Design Award-winning United luminaire continues to be a testament to the simple beauty of the fluorescent lamp. That being said, this LED luminaire is anything but ordinary, with a U-shaped housing that is both ceiling and wall-mountable. The light tubes of United are slightly recessed into the housing, emitting light on all sides, including both ends.


TM30 & CRI diagram



Light distribution & beam diagram



Decorative Accessories



- 13395109** Cover 974 2x United White Structure
- 13395132** Cover 974 2x United Black Structure

Choose a required accessory