


|          |
|----------|
| Date     |
| Customer |
| Project  |
| Type     |

*FFD\_United Asy Surface 1274 1x LED 3000K 1-10V DI Black Matt*

Our Good Design Award-winning United luminaire continues to be a testament to the simple beauty of the fluorescent lamp. That being said, this LED luminaire is anything but ordinary, with a U-shaped housing that is both ceiling and wall-mountable. The light tubes of United are slightly recessed into the housing, emitting light on all sides, including both ends.



### Specifications

|                                 |                      |
|---------------------------------|----------------------|
| Material                        | 13400402             |
| Light Source Type               | LED                  |
| LED Type                        | NLP                  |
| LED technology                  | LED PCB              |
| CRI                             | Min. 90              |
| Colour Temperature              | 3000K                |
| Lifetime                        | L80B10 @50,000 Hours |
| Lamp Included                   | Yes                  |
| Number of Light Sources         | 1                    |
| Binning (SDCM)                  | 2                    |
| Light Direction                 | Down                 |
| Input Voltage                   | 230V                 |
| Luminaire power (W)             | 22.0                 |
| Electrical Class                | I                    |
| IP Rating                       | 20                   |
| Glow wire rating (°C)           | 960                  |
| Dimming Protocol                | 1-10V                |
| Indoor/Outdoor                  | Indoor               |
| Application                     | Ceiling, Wall        |
| Mounting                        | Surface              |
| Adjustability                   | Not Applicable       |
| Distance to Lighted Object (m)  | 0,1                  |
| Primary Colour & Primary Finish | Black, Matt          |
| Gross weight (g)                | 2260.0               |
| Luminous flux per lamp (lm)     | 1022                 |
| Efficacy (lm/W)                 | 46                   |
| Glare rating                    | 24                   |

### TM30 & CRI diagram



### Light distribution & beam diagram

