


Pate
Customer
Project
уре

Pista Linear Light Track 48V 1555 1x LED 2700K Non-Dim White Structure



Pista is the ultimate in modern aesthetics that introduces thinner and slimmer magnetic track rails, ever smaller light fixtures and ultra-thin cables. Designers can play with different modules on single or multiple track rails in different lengths and colours. The geometrical possibilities are endless.





$\alpha \cdot c \cdot \ldots$	
Specificatio	ns

Specifications	
Material	13412209
Light Source Type	LED
LED Type	PISTA LINEAR (FLAPS)
LED technology	LED flexible PCB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	52 82 97 100 61
Binning (SDCM)	3
Input Voltage	48Vdc
Luminaire power (W)	25.5
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Non-Dim
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	678.0
Delivered lumens (lm)	1478
Efficacy (Im/W)	57
Glare rating	26
Remark	 3500K and 4000K on request White Pista Track 48V linear modules come with a white track adapter. All other Pista Track 48V linear modules have a black track adapter. Exceptions are only possible on request. This is not a complete product. Pista track 48V system required. For installations without dimmer, it is

recommended to use 1-10 V luminaires.



TM30 & CRI diagram





Light distribution & beam diagram

