


Pate	
Customer	
Project	
уре	

Pista Linear Light Track 48V 555 1x LED 3000K Non-Dim White Structure



Pista is the ultimate in modern aesthetics that introduces thinner and slimmer magnetic track rails, ever smaller light fixtures and ultra-thin cables. Designers can play with different modules on single or multiple track rails in different lengths and colours. The geometrical possibilities are endless.





Sne	rific	ati	ons	

Specifications			
Material	13412509		
Light Source Type	LED		
LED Type	PISTA LINEAR (FLAPS)		
LED technology	LED flexible PCB		
CRI	Min. 90		
Colour Temperature	3000K		
Lifetime	L80B10 @50,000 Hours		
Lamp Included	Yes		
Number of Light Sources	1		
CIE flux code	52 82 97 100 61		
Binning (SDCM)	3		
Input Voltage	48Vdc		
Luminaire power (W)	8.5		
Electrical Class			
IP Rating	20		
Glow wire rating (°C)	960		
Dimming Protocol	Non-Dim		
Indoor/Outdoor	Indoor		
Application	Ceiling, Wall		
Adjustability	Not Applicable		
Distance to Lighted Object (m)	0,1		
Primary Colour & Primary Finish	White, Structure		
Gross weight (g)	249.0		
Delivered lumens (Im)	517		
Efficacy (Im/W)	60		
Glare rating	27		
Remark	 3500K and 4000K on request White Pista Track 48V linear modules come with a white track adapter. All other Pista Track 48V linear modules have a black track adapter. Exceptions are only possible on request. This is not a complete product. Pista track 48V system required. 		

- For installations without dimmer, it is recommended to use 1-10 V luminaires.



TM30 & CRI diagram





Light distribution & beam diagram

