


| Date     |
|----------|
| Customer |
| Project  |
| уре      |

## Pista Linear Light Track 48V 636 1x LED 3000K 1-10V White Structure



Pista is the ultimate in modern aesthetics that introduces thinner and slimmer magnetic track rails, ever smaller light fixtures and ultra-thin cables. Designers can play with different modules on single or multiple track rails in different lengths and colours. The geometrical possibilities are endless.





| Specifications                  |   |
|---------------------------------|---|
| Material Material               | 13413509  |
| Light Source Type               | LED   |
| LED Type                        | PISTA LINEAR (FLAPS)  |
| LED technology                  | LED flexible PCB  |
| CRI                             | Min. 90   |
| Colour Temperature              | 3000K   |
| Lifetime                        | L80B10 @50,000 Hours  |
| Lamp Included                   | Yes   |
| Number of Light<br>Sources      | 1   |
| CIE flux code                   | 52 82 97 100 61   |
| Binning (SDCM)                  | 3   |
| Light Direction                 | Down  |
| Input Voltage                   | 48Vdc   |
| Luminaire power (W)             | 8.5   |
| Electrical Class                | III   |
| IP Rating                       | 20  |
| Glow wire rating (°C)           | 960   |
| Dimming Protocol                | 1-10V   |
| Indoor/Outdoor                  | Indoor  |
| Application                     | Ceiling, Wall   |
| Adjustability                   | Not Applicable  |
| Distance to Lighted Object (m)  | 0,1   |
| Primary Colour & Primary Finish | White, Structure  |
| Gross weight (g)                | 546.0   |
| Luminous flux per lamp (Im)     | 517   |
| Efficacy (Im/W)                 | 60  |
| Glare rating                    | 27  |
| Remark                          | <ul> <li>3500K and 4000K on request</li> <li>White Pista Track 48V linear modules come with a white track adapter. All other Pista Track 48V linear modules have a black track adapter. Exceptions are only possible on request.</li> <li>This is not a complete product. Pista track 48V system required.</li> </ul> |

• For installations without dimmer, it is recommended to use 1-10 V luminaires.



## TM30 & CRI diagram





## Light distribution & beam diagram

