

---




---



---




---

*Pista Linear Light Track 48V 2136 lx LED 2700K DALI Black Structure*

**Specifications**

Material	13414332
Light Source Type	LED
LED Type	PISTA LINEAR (FLAPS)
LED technology	LED flexible PCB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	52 82 97 100 61
Binning (SDCM)	3
Light Direction	Down
Input Voltage	48Vdc
Luminaire power (W)	34.0
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI
DALI Standard	DALI version-1
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	1469.0
Luminous flux per lamp (lm)	1970
Efficacy (lm/W)	57
Glare rating	26
Remark	<ul style="list-style-type: none"> <li>• 3500K and 4000K on request</li> <li>• White Pista Track 48V linear modules come with a white track adapter. All other Pista Track 48V linear modules have a black track adapter. Exceptions are only possible on request.</li> <li>• This is not a complete product. Pista track 48V system required.</li> <li>• For installations without dimmer, it is recommended to use 1-10 V luminaires.</li> </ul>

Pista is the ultimate in modern aesthetics that introduces thinner and slimmer magnetic track rails, ever smaller light fixtures and ultra-thin cables. Designers can play with different modules on single or multiple track rails in different lengths and colours. The geometrical possibilities are endless.



**TM30 & CRI diagram**

**Light distribution & beam diagram**
