


Date
Customer
Project
Type

Pista Linear Light Track 48V 2636 1x LED 2700K DALI Black Structure




Specifications

Material	13414432
Light Source Type	LED
LED Type	PISTA LINEAR (FLAPS)
LED technology	LED flexible PCB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	52 82 97 100 61
Binning (SDCM)	3
Light Direction	Down
Input Voltage	48Vdc
Luminaire power (W)	42.5
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI
DALI Standard	DALI version-1
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	2010.0
Delivered lumens (lm)	2463
Efficacy (lm/W)	57
Glare rating	26
Remark	<ul style="list-style-type: none"> • 3500K and 4000K on request • White Pista Track 48V linear modules come with a white track adapter. All other Pista Track 48V linear modules have a black track adapter. Exceptions are only possible on request. • This is not a complete product. Pista track 48V system required. • For installations without dimmer, it is recommended to use 1-10 V luminaires.

Pista is the ultimate in modern aesthetics that introduces thinner and slimmer magnetic track rails, ever smaller light fixtures and ultra-thin cables. Designers can play with different modules on single or multiple track rails in different lengths and colours. The geometrical possibilities are endless.

TM30 & CRI diagram



Light distribution & beam diagram

