


| Pate |
|----------|
| Customer |
| Project |
| уре |

FFD_Pista Linear Nightlight Track 48V 1136 1x LED 2700K DALI Black Structure

Pista is the ultimate in modern aesthetics that introduces thinner and slimmer magnetic track rails, ever smaller light fixtures and ultra-thin cables. Designers can play with different modules on single or multiple track rails in different lengths and colours. The geometrical possibilities are endless.





| Specifications | |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material | 13417132 |
| Light Source Type | LED |
| LED Type | PISTA LINEAR (FLAPS) |
| LED technology | LED flexible PCB |
| CRI | Min. 90 |
| Colour Temperature | 2700K |
| Lifetime | L80B10 @50,000 Hours |
| Lamp Included | Yes |
| Number of Light Sources | 1 |
| Binning (SDCM) | 3 |
| Light Direction | Down |
| Input Voltage | 48Vdc |
| Luminaire power (W) | 17.0 |
| Electrical Class | III |
| IP Rating | 20 |
| Glow wire rating (°C) | 960 |
| Dimming Protocol | DALI |
| DALI Standard | DALI version-1 |
| Indoor/Outdoor | Indoor |
| Application | Ceiling, Wall |
| Adjustability | Not Applicable |
| Distance to Lighted Object (m) | 0,1 |
| Primary Colour & Primary Finish | Black, Structure |
| Gross weight (g) | 737.0 |
| Delivered lumens (lm) | 161 |
| Efficacy (Im/W) | 9 |
| Glare rating | 20 |
| Remark | 3500K and 4000K on request This black Track 48V linear module comes with a black track adapter. Exceptions are only possible on request. This is not a complete product. Pista track 48V system required. For installations without dimmer, it is recommended to use 1-10 V luminaires. |



TM30 & CRI diagram





Light distribution & beam diagram

