


Date
Customer
Project
Туре

## Marbulito Track 48V Adjustable 41 2x LED 2700K Medium 1-10V White Structure



As a luminaire component for our redesigned Modupoint LED, Marbulito makes a big entrance. Suspended on a long cable, or plugged into Modupoint LED's ceiling base with a short or longer extender stick. In black or in white structure. You'll be seeing pearls of Marbulitos in all kinds of spaces.






12/21000

S	p	e	c	ij	fic	ca	lti	io	ns	3

Material	13421009
Light Source Type	LED
LED Type	CREE 1304
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	99 100 100 100 72
Binning (SDCM)	2
Light Direction	Down
Optic	Lens
Measured beam angle (°)	26.0
Input Voltage	48Vdc
Luminaire power (W)	10.5
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	1-10V
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	H 360° V 50°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	275.0
Delivered lumens (Im)	332
Efficacy (Im/W)	63
Glare rating	17

Remark

- 4000K on request
- White Pista 48V luminaires have a white track adapter. All other Pista 48V luminaires have a black track adapter. Deviation from this is only possible on request.
- This Track 48V luminaire can not be used in the upper part of a Pista Track 48V Profile Suspended Up/Down.
- This is not a complete product. Pista track 48V






system required.

• For installations without dimmer, it is recommended to use 1-10 V luminaires.



## TM30 & CRI diagram





## Light distribution & beam diagram

