


Date
Customer
Project
Туре

Marbulito Track 48V Suspended 41 1x LED 2700K Medium 1-10V Black Structure



As a luminaire component for our redesigned Modupoint LED, Marbulito makes a big entrance. Suspended on a long cable, or plugged into Modupoint LED's ceiling base with a short or longer extender stick. In black or in white structure. You'll be seeing pearls of Marbulitos in all kinds of spaces.






Sp	ecij	fic	ati	ons	3
	<u> </u>				_

Material	13422032	
Light Source Type	LED	
LED Type	CREE 1304	
LED technology	LED COB	
CRI	Min. 90	
Colour Temperature	2700K	
Lifetime	L90B10 @50,000 Hours	
Lamp Included	Yes	
Number of Light Sources	1	
CIE flux code	99 100 100 100 72	
Binning (SDCM)	2	
Light Direction	Down	
Optic	Lens	
Measured beam angle (°)	26.0	
Input Voltage	48Vdc	
Luminaire power (W)	6.5	
Electrical Class	III	
IP Rating	20	
Glow wire rating (°C)	960	
Dimming Protocol	1-10V	
Indoor/Outdoor	Indoor	
Application	Ceiling	
Mounting	Suspended	
Adjustability	Not Applicable	
Distance to Lighted Object (m)	0,1	
Primary Colour & Primary Finish	Black, Structure	
Gross weight (g)	347.0	
Delivered lumens (Im)	332	
Efficacy (Im/W)	51	
Glare rating	17	
Remark	 This is not a complete product. Pista track 48V system required. For installations without dimmer, it is recommended to use 1-10 V luminaires. 	



TM30 & CRI diagram





Light distribution & beam diagram

