


Date
Customer
Project
Type

Medard Semi-Recessed Adjustable 42 1x LED 2700K Medium DE Black Structure




The quirky long legs of the praying mantis inspired the Dutch Basten Leijh Design Studio for the creation of Medard, its initial design being a stylish table lamp. Now a large, versatile family of accent lights, and a lot of flexibility, Medard opens into a multitude of elegant applications.



Specifications

Material	13432032
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G7
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 68
Binning (SDCM)	2
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	25.0
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Semi-Recessed
Cut-out size (mm)	ø44
Mounting depth (mm)	70.0
Adjustability	H 355° V 360°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	241.0
Drive current (mA)	350 500 700
Min. forward voltage (Vf)	14.8 15.2 15.9
Max. forward voltage (Vf)	18.0 18.6 19.5
Connected load (W)	5.7 8.5 12.4
Delivered lumens (lm)	487 657 852
Efficacy (lm/W)	86 77 69
Glare rating	11 12 13
Remark	• 3500K and 4000K on request

TM30 & CRI diagram



Light distribution & beam diagram

