


Date
Customer
Project
Type

*Medard Semi-Recessed Adjustable 42 1x LED 3000K Flood DE Black Structure*



**Specifications**

Material	13432332
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G7
LED technology	LED COB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 71
Binning (SDCM)	2
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	37.0
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Semi-Recessed
Cut-out size (mm)	ø44
Mounting depth (mm)	70.0
Adjustability	H 355° V 360°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	241.0
Drive current (mA)	350      500      700
Min. forward voltage (Vf)	14,8      15,2      15,9
Max. forward voltage (Vf)	18,0      18,6      19,5
Connected load (W)	5,7      8,5      12,4
Luminous flux per lamp (lm)	516      695      901
Efficacy (lm/W)	91      82      73
Glare rating	14      15      16

The quirky long legs of the praying mantis inspired the Dutch Basten Leijh Design Studio for the creation of Medard, its initial design being a stylish table lamp. Now a large, versatile family of accent lights, and a lot of flexibility, Medard opens into a multitude of elegant applications.

---

Remark

- 3500K and 4000K on request
-

**TM30 & CRI diagram**



**Light distribution & beam diagram**



Diagrams

**Installation Accessories**



**12293730** Plaster Kit 44 1x

Choose a required accessory