


Date
Customer
Project
Type

Medard Semi-Recessed Adjustable 42 1x LED 1800-3000K WD Flood DE Black Structure



Specifications


Material	13432532
Light Source Type	LED
LED Type	BRIDGELUX WARMDIM 6W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	39.3
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Semi-Recessed
Cut-out size (mm)	ø44
Mounting depth (mm)	70.0
Adjustability	H 355° V 360°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	241.0
Drive current (mA)	350
Min. forward voltage (Vf)	15,5
Max. forward voltage (Vf)	18,5
Connected load (W)	6,0
Luminous flux per lamp (lm)	364
Efficacy (lm/W)	60
Glare rating	16
Remark	• 3500K and 4000K on request

The quirky long legs of the praying mantis inspired the Dutch Basten Leijh Design Studio for the creation of Medard, its initial design being a stylish table lamp. Now a large, versatile family of accent lights, and a lot of flexibility, Medard opens into a multitude of elegant applications.

TM30 & CRI diagram



Light distribution & beam diagram



Diagrams

Installation Accessories



12293730 Plaster Kit 44 1x

Choose a required accessory