


Date
Customer
Project
Туре

Medard Track 48V Adjustable 42 1x LED 1800-3000K WD Flood 1-10V White Structure



The quirky long legs of the praying mantis inspired the Dutch Basten Leijh Design Studio for the creation of Medard, its initial design being a stylish table lamp. Now a large, versatile family of accent lights, and a lot of flexibility, Medard opens into a multitude of elegant applications.





13433109

a					r.								
Δ	\boldsymbol{n}	e	c	11	7.	c	a	Ŧ.	1	O	п	S	
\sim	ρ .	•	~	٠.)			90		4	~		~	

Material

Material	13433109
Light Source Type	LED
LED Type	BRIDGELUX WARMDIM 6W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	39.3
Input Voltage	48Vdc
Luminaire power (W)	8.0
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	1-10V
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	H 360° V 360°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	320.0
Drive current (mA)	350
Luminous flux per lamp (lm)	364
Efficacy (Im/W)	45
Glare rating	16
Remark	3500K and 4000K on request

- White Pista 48V luminaires have a white track adapter. All other Pista 48V luminaires have a black track adapter. Deviation from this is only possible on request.
- This is not a complete product. Pista track 48V system required.
- For installations without dimmer, it is



Medard Track 48V Adjustable 42 1x LED 1800-3000K WD Flood 1-10V White Structure

recommended to use 1-10 V luminaires.



TM30 & CRI diagram





Light distribution & beam diagram

