


Pate
Customer
Project
уре

## FFD\_Pista Linear Light Flaps Track 48V 2136 1x LED 3000K 1-10V DI White Structure



Pista is the ultimate in modern aesthetics that introduces thinner and slimmer magnetic track rails, ever smaller light fixtures and ultra-thin cables. Designers can play with different modules on single or multiple track rails in different lengths and colours. The geometrical possibilities are endless.





Cn	oci	fil	at	ioi	2 0	

1 2	
Material	13450809
Light Source Type	LED
LED Type	PISTA LINEAR (FLAPS)
LED technology	LED flexible PCB
CRI	Min. 90
Colour Temperature	3000K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	59 86 97 100 75
Binning (SDCM)	3
Light Direction	Down
Optic	Lens
Input Voltage	48Vdc
Luminaire power (W)	34.0
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	1-10V
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	1693.0
Delivered lumens (lm)	2548
Efficacy (Im/W)	74
Glare rating	26
Remark	<ul> <li>3500K and 4000K on request</li> </ul>

Remark

- 3500K and 4000K on request
- This white Track 48V linear module comes with a white track adapter. Exceptions are only possible on request.
- This Track 48V luminaire can not be used in the upper part of a Pista Track 48V Profile Suspended Up/Down.
- This is not a complete product. Pista track 48V system required.
- For installations without dimmer, it is recommended to use 1-10 V luminaires.





Modular L.I. reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly Latest datasheet and documentation available on www.supermodular.com - 2025-07-17, 06:29:17 PM - @Modular Lighting Instruments



## TM30 & CRI diagram





## Light distribution & beam diagram

