

D	а	t	е		
С	11	S	to	m	e


ustomer

Project

Туре

FFD_Pista Linear Light Flaps Track 48V 1636 1x LED 3000K DALI DI Black Structure

Pista is the ultimate in modern aesthetics that introduces thinner and slimmer magnetic track rails, ever smaller light fixtures and ultra-thin cables. Designers can play with different modules on single or multiple track rails in different lengths and colours. The geometrical possibilities are endless.



Specifications				
Material	13451732			
Light Source Type	LED			
LED Type	PISTA LINEAR (FLAPS)			
LED technology	LED flexible PCB			
CRI	Min. 90			
Colour Temperature	3000K			
Lifetime	L80B10 @50,000 Hours			
Lamp Included	Yes			
Number of Light Sources	1			
CIE flux code	68 93 99 100 45			
Binning (SDCM)	3			
Light Direction	Down			
Optic	Reflector			
Input Voltage	48Vdc			
Luminaire power (W)	25.5			
Electrical Class	III			
IP Rating	20			
Glow wire rating (°C)	960			
Dimming Protocol	DALI			
DALI Standard	DALI version-1			
Indoor/Outdoor	Indoor			
Application	Ceiling, Wall			
Adjustability	Not Applicable			
Distance to Lighted Object (m)	0,1			
Primary Colour & Primary Finish	Black, Structure			
Gross weight (g)	1451.0			
Delivered lumens (lm)	1146			
Efficacy (Im/W)	44			
Glare rating	14			
Remark	 3500K and 4000K on request This black Track 48V linear module comes with a black track adapter. Exceptions are only possible on request. This Track 48V luminaire can not be used in the upper part of a Pista Track 48V Profile Suspended Up/Down. This is not a complete product. Pista track 48V system required. For installations without dimmon it is 			

• For installations without dimmer, it is



recommended to use 1-10 V luminaires.



TM30 & CRI diagram





Light distribution & beam diagram

