





Date
Customer
Project
Type



Marbul Track 230V Adjustable 109 Ix LED 1800-3000K WD DALI DI White Structure



Specifications

Material	13500209
Light Source Type	LED
LED Type	BRIDGELUX WARM DIM 12W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	100 100 100 100 94
Binning (SDCM)	3
Light Direction	Down
Input Voltage	230V
Luminaire power (W)	14.5
Electrical Class	II
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI
DALI Standard	DALI-2
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	H 360° V 45°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	1273.0
Drive current (mA)	350
Luminous flux per lamp (lm)	955
Efficacy (lm/W)	65
Glare rating	14
Remark	<ul style="list-style-type: none">• 4000K on request• Magnetic reflector not included• 4000K on request• This is not a complete product. Magnetic reflector and track 230V system required.• This is not a complete product. Magnetic reflector and track 230V system required.

Marbul is a timeless, spherical accent luminaire. Its pure geometrical shape makes it easily fit in every interior. Why designers love it so? The attention to detail and the simplicity of the shape present a minimalist, elegant and versatile design for those looking to experiment with organic lighting.

TM30 & CRI diagram

Light distribution & beam diagram


Optical Accessories

 **10219330** Reflector 82 Medium WD Aluminium Anodised

 **10219630** Reflector 82 Flood WD Gold Anodised

 **10219430** Reflector 82 Flood WD Aluminium Anodised

 **10219830** Reflector 82 Flood WD Champagne Anodised

 Choose a required accessory