


| |
|----------|
| Date |
| Customer |
| Project |
| Type |

Tetrix Oblique Recessed 62 1x IP55 LED 3000K Medium DE Black Chrome



Playing with pieces, fitting them together in all kinds of intricate ways. Tetrix invites you to give it your personal touch with design options and accessories. It's versatile, fits everywhere, and is a breeze to install.



Specifications

| | |
|---------------------------------|---|
| Material | 13512280 |
| Light Source Type | LED |
| LED Type | BRIDGELUX V8G8 |
| LED technology | LED COB |
| CRI | Min. 90 |
| Colour Temperature | 3000K |
| Lifetime | L90B10 @50,000 Hours |
| Lamp Included | Yes |
| Number of Light Sources | 1 |
| CIE flux code | 100 100 100 100 94 |
| Binning (SDCM) | 2 |
| Light Direction | Down |
| Optic | Collimator |
| Measured beam angle (°) | 25.2 |
| Input Voltage | Constant Current Driver Required |
| Electrical Class | III |
| IP Rating | 55 |
| Glow wire rating (°C) | 850 |
| Indoor/Outdoor | Indoor |
| Application | Ceiling, Wall |
| Mounting | Recessed |
| Cut-out size (mm) | ø68 for Frame Recessed; ø89 for Frame Recessed TrimLess |
| Mounting depth (mm) | 110.0 |
| Adjustability | Not Applicable |
| Distance to Lighted Object (m) | 0,1 |
| Primary Colour & Primary Finish | Black, Chrome |
| Gross weight (g) | 148.0 |
| Drive current (mA) | 350 500 |
| Min. forward voltage (Vf) | 13,2 13,7 |
| Max. forward voltage (Vf) | 15,0 15,4 |
| Connected load (W) | 5,0 7,2 |
| Delivered lumens (lm) | 495 670 |
| Efficacy (lm/W) | 99 93 |
| Glare rating | 7 8 |
| Remark | • Tetrix Recessed Ring or Tube Surface not |




included

- This is not a complete product. Tetrix Recessed Ring or Tube Surface required.
 - This is not a complete product. Tetrix Recessed Ring or Tube Surface required.
-


TM30 & CRI diagram




Light distribution & beam diagram




Optical Accessories



13515032 Snoot 32 Black Structure
13515038 Snoot 32 White Matt




13515132 Honeycomb 33 Black Structure




13515232 Light Cone 44 Black Structure
13515238 Light Cone 44 White Matt


Installation Accessories




13510083 Ring Recessed 62 1x IP55 Black Matt
13510038 Ring Recessed 62 1x IP55 White Matt




13515430 Ring Recessed Trimless 62 1x




13515530 Concrete Kit 62 150x150 1x




13515630 Concrete Ring 62 Standard Installation Housing




12293230 Plaster Kit Trimless 150x150 - 62 1x




12293330 Plaster Kit Trimless 300x150 - 62 2x




11624030 Installation Housing 140x250x100x210



11624130 Installation Housing 140x400x100x210



12292630 Gypsum Fibreboard 150x150



12292730 FFD_Gypsum fibreboard 300x150

Choose a required accessory