


Date
Customer
Project
Type

*Extruded Suspended 46 900 1x LED 1800-3000K WD Flood DE Grey White Structure - Grey White Matt*



This statement luminaire loves to play with light when it's on and when it's off. Its strong lines bring vertical structure to your space. The grooves along the shaft tell a different tale, every time the surrounding light changes. A cone-shape lampshade offers glare-free, intimate, accent light. Extruded is made for exchange. People to people, light to shadow.



### Specifications

Material	13520836
Light Source Type	LED
LED Type	BRIDGELUX WARMDIM 6W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	97 100 100 100 83
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	47.3
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling
Mounting	Suspended
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Grey White, Structure
Secondary Colour & Secondary Finish	Grey White, Matt
Gross weight (g)	2365.0
Drive current (mA)	350
Min. forward voltage (Vf)	15,5
Max. forward voltage (Vf)	18,5
Connected load (W)	6,0
Luminous flux per lamp (lm)	418
Efficacy (lm/W)	70
Glare rating	23

---


Remark

- Suspension kit not included
  - Suspension kit not included
  - Longer suspension cable on request (standard length is 2 meter)
  - When used in combination with Kompas Round Surface: Suspension Point for Kompas required.
  - This is not a complete product. Suspension kit required.
-


**TM30 & CRI diagram**



**Light distribution & beam diagram**




**Installation Accessories**




■ **13523632** Power Feed and Suspension Canopy Surface Round Extruded Trailing Edge DI 350mA (Incl. Suspension Cable 2000) Black Structure

■ **13523636** Power Feed and Suspension Canopy Surface Round Extruded Trailing Edge DI 350mA (Incl. Suspension Cable 2000) Grey White Matt



■ **13523032** Power Feed and Suspension Canopy Semi-Recessed Round 2P Extruded DE (Incl. Suspension Cable 2000) Black Structure

■ **13523036** Power Feed and Suspension Canopy Semi-Recessed Round 2P Extruded DE (Incl. Suspension Cable 2000) Grey White Matt



■ **13523132** Power Feed and Suspension Canopy Surface Round 2P Extruded DE (Incl. Suspension Cable 2000) Black Structure

■ **13523136** Power Feed and Suspension Canopy Surface Round 2P Extruded DE (Incl. Suspension Cable 2000) Grey White Structure

■ Choose a required accessory