


Date
Customer
Project
Type

## Kogel Surface Adjustable 58 2x LED 2700K DALI/Push-Dim DI White Structure





A spotlight with extremely flexible rotation, Kogel will leave you gasping in wonder. For starters, it uses a ball joint as a rotation mechanism. So yes, turning it all kinds of ways is possible. And no, the wires won't get all twisted inside. It just works and you'll love it on ceilings and walls. Designed by Odin and Jaap of Studio Kees, Kogel is truly a light that gives pleasure.




### Specifications

Material	13561209
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	98 100 100 100 66
Binning (SDCM)	2
Light Direction	Down
Input Voltage	230V
Luminaire power (W)	29.5
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI, Push-Dim
DALI Standard	DALI-2
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Surface
Adjustability	H 360° V 50°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	2190.0
Luminous flux per lamp (lm)	842
Efficacy (lm/W)	57
Glare rating	21
Remark	<ul style="list-style-type: none"> <li>• Magnetic reflector or lens not included.</li> <li>• This is not a complete product. Magnetic reflector or lens required.</li> <li>• This is not a complete product. Magnetic reflector or lens required.</li> </ul>


*TM30 & CRI diagram*



*Optical Accessories*



- 10222230 Reflector 51 Medium
- 10222330 Reflector 51 Flood



- 10222630 Lens 51 Spot
- 10222830 Lens 51 Flood
- 10222730 Lens 51 Medium
- 10222930 Lens 51 Wide Flood

Choose a required accessory