


Date
Customer
Project
Type

Kogel Surface Adjustable 58 2x LED 1800-3000K WD Trailing Edge DI White Structure




A spotlight with extremely flexible rotation, Kogel will leave you gasping in wonder. For starters, it uses a ball joint as a rotation mechanism. So yes, turning it all kinds of ways is possible. And no, the wires won't get all twisted inside. It just works and you'll love it on ceilings and walls. Designed by Odin and Jaap of Studio Kees, Kogel is truly a light that gives pleasure.




Specifications

Material	13561809
Light Source Type	LED
LED Type	BRIDGELUX WARMDIM 8W
LED technology	LED COB
CRI	Min. 95
Colour Temperature	1800-3000K (Warm Dim)
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	2
CIE flux code	96 99 99 100 67
Binning (SDCM)	3
Light Direction	Down
Input Voltage	230V
Luminaire power (W)	19.3
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	Trailing Edge
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Surface
Adjustability	H 360° V 50°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	2190.0
Luminous flux per lamp (lm)	600
Efficacy (lm/W)	62
Glare rating	20
Remark	<ul style="list-style-type: none"> • Magnetic reflector or lens not included. • This is not a complete product. Magnetic reflector or lens required. • This is not a complete product. Magnetic reflector or lens required.

TM30 & CRI diagram



Optical Accessories



- 10222430 Reflector 51 Medium WD
- 10222530 Reflector 51 Flood WD

Choose a required accessory