


Date
Customer
Project
Type

*Kogel Surface Adjustable 58 1x LED 2700K DALI/Push-Dim DI White Structure*



A spotlight with extremely flexible rotation, Kogel will leave you gaping in wonder. For starters, it uses a ball joint as a rotation mechanism. So yes, turning it all kinds of ways is possible. And no, the wires won't get all twisted inside. It just works and you'll love it on ceilings and walls. Designed by Odin and Jaap of Studio Kees, Kogel is truly a light that gives pleasure.



**Specifications**


Material	13560209
Light Source Type	LED
LED Type	BRIDGELUX V6 HD G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	98 100 100 100 66
Binning (SDCM)	2
Light Direction	Down
Input Voltage	230V
Luminaire power (W)	16.1
Electrical Class	I
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI, Push-Dim
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Surface
Adjustability	H 360° V 50°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	1414.0
Delivered lumens (lm)	842
Efficacy (lm/W)	52
Glare rating	21

Specifications

TM30 &amp; CRI diagram




Light distribution &amp; beam diagram



Diagrams

*Optical Accessories*



- **10219930** Magnetic reflector ø51 LED spot alu
- **10220030** Magnetic reflector ø51 LED medium alu
- **10220130** Magnetic reflector ø51 LED flood alu

■ Choose a required accessory