


Date
Customer
Project
Type

*Gamin Track 48V 90 lx LED 2700K DALI Black Structure*



Bring harmony and happiness to your space. Explore endless planetary configurations for your concept with our spherical luminaire, Gamin, and enjoy its soft, diffuse light. Unify your expression while keeping it unique, with variants of Placebo and/or Shellby.



**Specifications**

Material	13600132
Light Source Type	LED
LED Type	BRIDGELUX V8G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	27 53 78 65 67
Binning (SDCM)	2
Light Direction	Down
Input Voltage	48Vdc
Luminaire power (W)	8.5
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Dimming Protocol	DALI
DALI Standard	DALI-2
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	422.0
Luminous flux per lamp (lm)	588
Efficacy (lm/W)	69
Glare rating	23
Remark	<ul style="list-style-type: none"> <li>• This is not a complete product. Pista track 48V system required.</li> <li>• For installations without dimmer, it is recommended to use 1-10 V luminaires.</li> </ul>

**TM30 & CRI diagram**



**Light distribution & beam diagram**

