


Date
Customer
Project
Type

Minude Out Recessed 49 23 1x IP54 LED 2700K Medium DE Black Structure



Minude's yogic flexibility will surprise you about as much as its bare, cylindrical design. Express a refined and minimalistic look & feel on walls, on high or low ceilings. Try more than one Minude on our Pista track or on our redesigned Modupoint LED. Its long string of colours and miniature size will make a big impression.



Specifications

Material	13641032	
Light Source Type	LED	
LED Type	BRIDGELUX V6 HD G7	
LED technology	LED COB	
CRI	Min. 90	
Colour Temperature	2700K	
Lifetime	L80B10 @50,000 Hours	
Lamp Included	Yes	
Number of Light Sources	1	
CIE flux code	100 100 100 100 61	
Binning (SDCM)	2	
Light Direction	Down	
Optic	Lens	
Measured beam angle (°)	29.0	
Input Voltage	Constant Current Driver Required	
Electrical Class	III	
IP Rating	54	
Glow wire rating (°C)	960	
Indoor/Outdoor	Indoor	
Application	Ceiling, Wall	
Mounting	Recessed	
Cut-out size (mm)	ø44	
Mounting depth (mm)	80.0	
Adjustability	Not Applicable	
Distance to Lighted Object (m)	0,1	
Primary Colour & Primary Finish	Black, Structure	
Gross weight (g)	197.0	
Drive current (mA)	350	500
Min. forward voltage (Vf)	14.8	15.2
Max. forward voltage (Vf)	18.0	18.6
Connected load (W)	5.7	8.5
Delivered lumens (lm)	435	587
Efficacy (lm/W)	76	69
Glare rating	1	1

TM30 & CRI diagram




Light distribution & beam diagram


Minute Out Recessed 49 23 1x IP54 LED 2700K Medium DE Black Structure

Diagrams


Installation Accessories



12293730 Plaster Kit 44 1x



10889530 Installation Housing 123x100x80



12290730 Plaster Kit 100x120-45 1x

Choose a required accessory