


Pate
Customer
Project
уре

Minude Out Recessed 49 23 1x IP54 LED 2700K Medium DE Black Structure



Minude's yogic flexibility will surprise you about as much as its bare, cylindrical design. Express a refined and minimalistic look & feel on walls, on high or low ceilings. Try more than one Minude on our Pista track or on our redesigned Modupoint LED. Its long string of colours and miniature size will make a big impression.





Specifications				
Material	13641032			
Light Source Type	LED			
LED Type	BRIDGELUX V6 HD G7			
LED technology	LED COB			
CRI	Min. 90			
Colour Temperature	2700K			
Lifetime	L80B10 @	50,000 Hours		
Lamp Included	Yes			
Number of Light Sources	1			
CIE flux code	100 100 100 100 61			
Binning (SDCM)	2			
Light Direction	Down			
Optic	Lens			
Measured beam angle (°)	29.0			
Input Voltage	Constant Current Driver Required			
Electrical Class	III			
IP Rating	54			
Glow wire rating (°C)	960			
Indoor/Outdoor	Indoor			
Application	Ceiling, Wall			
Mounting	Recessed			
Cut-out size (mm)	ø44			
Mounting depth (mm)	80.0			
Adjustability	Not Applica	able		
Distance to Lighted Object (m)	0,1			
Primary Colour & Primary Finish	Black, Structure			
Gross weight (g)	197.0			
Drive current (mA)	350	500		
Min. forward voltage (Vf)	14,8	15,2		
Max. forward voltage (Vf)	18,0	18,6		
Connected load (W)	5,7	8,5		
Luminous flux per lamp (lm)	435	587		
Efficacy (Im/W)	76	69		
Glare rating	1	1		



TM30 & CRI diagram






Light distribution & beam diagram


Minude Out Recessed 49 23 1x IP54 LED 2700K Medium DE Black Structure			




Installation Accessories



12293730 Plaster Kit 44 1x



10889530 Installation Housing 123x100x80



12290730 Plaster Kit 100x120-45 1x

Choose a required accessory