


Pate
Customer
Project
уре

Minude Recessed 56 1x IP54 LED 2700K Medium DE Bronze Brushed Anodised



Minude's yogic flexibility will surprise you about as much as its bare, cylindrical design. Express a refined and minimalistic look & feel on walls, on high or low ceilings. Try more than one Minude on our Pista track or on our redesigned Modupoint LED. Its long string of colours and miniature size will make a big impression.





S	p	e	c	ij	fic	a	ti	0	ns	S
_										

Material	13650082					
Light Source Type	LED					
LED Type	BRIDGELUX V6 HD G7					
LED technology	LED COB					
CRI	Min. 90					
Colour Temperature	2700K					
Lifetime	L80B10 @50,000 Hours					
Lamp Included	Yes					
Number of Light Sources	1					
CIE flux code	100 100 100 100 62					
Binning (SDCM)	2					
Light Direction	Down					
Optic	Lens					
Measured beam angle (°)	29.0					
Input Voltage	Constant (Current Driver Required				
Electrical Class	III					
IP Rating	54					
Glow wire rating (°C)	960					
Indoor/Outdoor	Indoor					
Application	Ceiling, Wall					
Mounting	Recessed					
Cut-out size (mm)	ø51					
Mounting depth (mm)	100.0					
Adjustability	Not Applicable					
Distance to Lighted Object (m)	0,1					
Primary Colour & Primary Finish	Bronze, Brushed Anodised					
Gross weight (g)	190.0					
Drive current (mA)	350	500				
Min. forward voltage (Vf)	14,8	15,2				
Max. forward voltage (Vf)	18,0	18,6				
Connected load (W)	5,7	8,5				
Luminous flux per lamp (lm)	442	596				
Efficacy (Im/W)	78	70				
Glare rating	1	1				



TM30 & CRI diagram






Light distribution & beam diagram







Installation Accessories



12293830 Plaster Kit 51 1x



11624030 Installation Housing 140x250x100x210



12292630 Gypsum Fibreboard 150x150

Choose a required accessory