




Date
Customer
Project
Type



*K 72 Recessed 72 1x IP55 LED 2700K Flood DE Black Structure*




### Specifications

Material	14040232
Light Source Type	LED
LED Type	BRIDGELUX V8G8
LED technology	LED COB
CRI	Min. 90
Colour Temperature	2700K
Lifetime	L90B10 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
CIE flux code	95 100 100 100 90
Binning (SDCM)	2
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	32.0
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	55
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Recessed
Cut-out size (mm)	Ø65
Mounting depth (mm)	60.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	189.0
Drive current (mA)	350 500
Min. forward voltage (Vf)	13,2 13,7
Max. forward voltage (Vf)	15,0 15,4
Connected load (W)	5,0 7,2
Luminous flux per lamp (lm)	497 668
Efficacy (lm/W)	99 93
Glare rating	20 21

Every project needs a spotlight for general lighting. K is our suggestion for those who like to keep things simple yet flexible. K comes in two sizes, 80 and 89 mm, with a flat or sloping edge, in aluminium, or with a white or black structure. Available with halogen and LED. Choose the directional model for a greater interplay of light and more versatility.


**TM30 & CRI diagram**

**Light distribution & beam diagram**


### *Decorative Accessories*



**14042009** K-Set 72 1x White Structure


**14042032** K-Set 72 1x Black Structure




**14042109** K-Set 72 2x White Structure

**14042132** K-Set 72 2x Black Structure

### *Installation Accessories*



**10490330** Installation Housing 172x112x100



**12291330** Plaster Kit 170x112 - 65 1x

Choose a required accessory