

Date
Customer
Project
Type

K 72 Recessed 72 lx IP55 LED 4000K Spot DE Black Structure



Specifications


Material	14040632
Light Source Type	LED
LED Type	BRIDGELUX V8G6
LED technology	LED COB
CRI	Min. 90
Colour Temperature	4000K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	15.5
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	55
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Recessed
Cut-out size (mm)	ø65
Mounting depth (mm)	60.0
Adjustability	Not Applicable
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	Black, Structure
Gross weight (g)	189.0
Drive current (mA)	350 500
Min. forward voltage (Vf)	16,5 17,1
Max. forward voltage (Vf)	19,2 19,8
Connected load (W)	6,2 9,2
Luminous flux per lamp (lm)	560 704
Efficacy (lm/W)	90 77
Glare rating	20 21

Every project needs a spotlight for general lighting. K is our suggestion for those who like to keep things simple yet flexible. K comes in two sizes, 80Ø and 89Ø mm, with a flat or sloping edge, in aluminium, or with a white or black structure. Available with halogen and LED. Choose the directional model for a greater interplay of light and more versatility.

TM30 & CRI diagram



Light distribution & beam diagram



Decorative Accessories



- 14042009** K-Set 72 1x White Structure
- 14042032** K-Set 72 1x Black Structure



- 14042109** K-Set 72 2x White Structure
- 14042132** K-Set 72 2x Black Structure

Installation Accessories



- 10490330** Installation Housing 172x112x100



- 12291330** Plaster Kit 170x112 - 65 1x

Choose a required accessory