




Date
Customer
Project
Type

K 72 Recessed 72 1x IP55 LED 4000K Medium DE White Structure






Every project needs a spotlight for general lighting. K is our suggestion for those who like to keep things simple yet flexible. K comes in two sizes, 80 and 89 mm, with a flat or sloping edge, in aluminium, or with a white or black structure. Available with halogen and LED. Choose the directional model for a greater interplay of light and more versatility.




Specifications



Material	14040709	
Light Source Type	LED	
LED Type	BRIDGELUX V8G6	
LED technology	LED COB	
CRI	Min. 90	
Colour Temperature	4000K	
Lifetime	L80B20 @50,000 Hours	
Lamp Included	Yes	
Number of Light Sources	1	
Binning (SDCM)	3	
Light Direction	Down	
Optic	Reflector	
Measured beam angle (°)	22.5	
Input Voltage	Constant Current Driver Required	
Electrical Class	III	
IP Rating	55	
Glow wire rating (°C)	960	
Indoor/Outdoor	Indoor	
Application	Ceiling, Wall	
Mounting	Recessed	
Cut-out size (mm)	Ø65	
Mounting depth (mm)	60.0	
Adjustability	Not Applicable	
Distance to Lighted Object (m)	0,1	
Primary Colour & Primary Finish	White, Structure	
Gross weight (g)	189.0	
Drive current (mA)	350	500
Min. forward voltage (Vf)	16,5	17,1
Max. forward voltage (Vf)	19,2	19,8
Connected load (W)	6,2	9,2
Luminous flux per lamp (lm)	582	731
Efficacy (lm/W)	94	79
Glare rating	21	22

TM30 & CRI diagram

Light distribution & beam diagram


Decorative Accessories

14042009 K-Set 72 1x White Structure

14042032 K-Set 72 1x Black Structure

14042109 K-Set 72 2x White Structure

14042132 K-Set 72 2x Black Structure

Installation Accessories

10490330 Installation Housing 172x112x100

12291330 Plaster Kit 170x112 - 65 1x

Choose a required accessory