


Date
Customer
Project
Type

FFD_K 77 Recessed Adjustable 77 1x LED 4000K Medium DE Donkey Grey Structure




Every project needs a spotlight for general lighting. K is our suggestion for those who like to keep things simple yet flexible. K comes in two sizes, 80 and 89 mm, with a flat or sloping edge, in aluminium, or with a white or black structure. Available with halogen and LED. Choose the directional model for a greater interplay of light and more versatility.




Specifications

Material	14050771	
Light Source Type	LED	
LED Type	BRIDGELUX V8G6	
LED technology	LED COB	
CRI	Min. 90	
Colour Temperature	4000K	
Lifetime	L80B20 @50,000 Hours	
Lamp Included	Yes	
Number of Light Sources	1	
Binning (SDCM)	3	
Light Direction	Down	
Optic	Reflector	
Measured beam angle (°)	22.5	
Input Voltage	Constant Current Driver Required	
Electrical Class	III	
IP Rating	20	
Glow wire rating (°C)	960	
Indoor/Outdoor	Indoor	
Application	Ceiling, Wall	
Mounting	Recessed	
Cut-out size (mm)	ø70	
Mounting depth (mm)	60.0	
Adjustability	H 360° V -30°/+30°	
Distance to Lighted Object (m)	0,1	
Primary Colour & Primary Finish	Donkey Grey, Structure	
Gross weight (g)	208.0	
Drive current (mA)	350	500
Min. forward voltage (Vf)	16,5	17,1
Max. forward voltage (Vf)	19,2	19,8
Connected load (W)	6,2	9,2
Luminous flux per lamp (lm)	549	690
Efficacy (lm/W)	88	75
Glare rating	20	21

TM30 & CRI diagram




Light distribution & beam diagram




Diagrams

Decorative Accessories



14052009 K-Set 77 1x White Structure


14052032 K-Set 77 1x Black Structure




14052109 K-Set 77 2x White Structure

14052132 K-Set 77 2x Black Structure

Installation Accessories



10889830 Installation Housing 192x190x130



12290130 Plaster Kit 190X190 - 70 1x

Choose a required accessory