


Date
Customer
Project
Type

*K 77 Recessed Adjustable 77 1x LED 4000K Flood DE White Structure*



**Specifications**


Material	14050809
Light Source Type	LED
LED Type	BRIDGELUX V8G6
LED technology	LED COB
CRI	Min. 90
Colour Temperature	4000K
Lifetime	L80B20 @50,000 Hours
Lamp Included	Yes
Number of Light Sources	1
Binning (SDCM)	3
Light Direction	Down
Optic	Reflector
Measured beam angle (°)	32.2
Input Voltage	Constant Current Driver Required
Electrical Class	III
IP Rating	20
Glow wire rating (°C)	960
Indoor/Outdoor	Indoor
Application	Ceiling, Wall
Mounting	Recessed
Cut-out size (mm)	ø70
Mounting depth (mm)	60.0
Adjustability	H 360° V -30°/+30°
Distance to Lighted Object (m)	0,1
Primary Colour & Primary Finish	White, Structure
Gross weight (g)	208.0
Drive current (mA)	350      500
Min. forward voltage (Vf)	16,5      17,1
Max. forward voltage (Vf)	19,2      19,8
Connected load (W)	6,2      9,2
Luminous flux per lamp (lm)	580      730
Efficacy (lm/W)	94      79
Glare rating	20      21

Every project needs a spotlight for general lighting. K is our suggestion for those who like to keep things simple yet flexible. K comes in two sizes, 80ø and 89ø mm, with a flat or sloping edge, in aluminium, or with a white or black structure. Available with halogen and LED. Choose the directional model for a greater interplay of light and more versatility.

**TM30 & CRI diagram**



**Light distribution & beam diagram**




Diagrams

**Installation Accessories**



**10889830** Installation Housing 192x190x130



**12290130** Plaster Kit 190X190 - 70 1x

Choose a required accessory